

EDGE FINDERS
STARRETT SERIES 827:



Work with flat, straight edges, shoulders, grooves, round work, studs, dowels, or center points and scribed lines can be accurately located with this handy tool. Double end model has a pointed contact at opposite end for locating center points and scribed lines. Body and contacts made of tool steel, hardened, ground and lapped to close tolerances for diameter and concentricity. Furnished in protective case.

Body Diameter	Contact Diameter	Description	Catalog No.	EDP No.	Price
.375"	.200"	Single End	827A	53062	
.500	.200 and pointed contact	Double End	827B	53063	
10mm	6mm	Single End	827MA	56041	

ROUND BAR CENTER FINDER
SERIES 250:



€Accurately and quickly locates center on round workpiece.
€For execution place the tool in drill chuck or collet and line up pointer with line scribed on shaft.
€Supplied with instructions



Order No.	Shank Dia.	Overall Length	Price
1700025	3/8"/9.5mm	4-1/8"/105mm	

STEREO MICROSCOPES
SERIES 510:



DELUXE FEATURES:

- Fully coated, excellent optics give an upright image over a wide field of view, sharp and clear
- Provides the original true color of the viewed object
- Accurate alignment ensures the observer fatigue-free viewing
- 45° inclined binocular head, with locked-in eyepieces.
- Left ocular-tube with diopter adjustment range of ±5mm
- Interpupillary distance adjustable between 2.16 - 2.95"
- Working distance 2.09"
- Includes paired eyecaps, a dust cover, paired clips
- Well-painted metal base
- Precise and smooth rack & pinion focus system
- Equipped with an arm stand.



Order No.	Price
5100600	

Eyepiece **WF10X**
Objective **2X / 4X**
Object Plate **White / black, glass, Ø3.74"**
Light Source **Top & bottom incandescent light**

Description	Order No.	Price
15X Eyepiece pair	5100515	
20X Eyepiece pair	5100520	

WIGGLER OR CENTER FINDER
SERIES 250:



The attachments permit this tool to be used for many different applications such as: checking concentricity, establishing center distances, positioning tool spindle in relation to work surfaces, etc. Set includes body and the following interchangeable attachments:

- Ball contact (.250" dia.)
- Disc contact (.100" Dia.)
- Needle point
- Offset indicator holder

Order No.	Price
1700500	

WIGGLER OR CENTER FINDER WITH ATTACHMENTS
STARRETT SERIES 828:




Wiggler/Center Finder, complete with Pointed Shank, Ball Contact, Disc Contact, Offset Indicator Holder, and Case.

- Furnished with offset indicator holder and chuck designed to hold all attachments.
- Four attachments adapt the tool to countless applications.
- Check run-out or concentricity; establish center distances, check straightness or alignment of flat surfaces.
- With Pointed Shank, working centers can be accurately located.

Catalog No.	EDP No.	Description	Price
S828HZ	53064	Wiggler/Center Finder, complete with case and 4 attachments	

See Our Entire Selection of:

MICROMETERS..... See index



HEIGHT GAGES See index





POCKET MICROSCOPE SERIES 510:



50 POWER
(Microscope has inverted image)


Model Number 2013	
Order No. 5105010	Price <input type="text"/>

FIBEROPTIC FLEXIBLE BORESCOPE

SERIES 986:

**GENERAL PURPOSE INDUSTRIAL SCOPE
HANDLING MULTIPLE INSPECTION TASKS**

General Purpose Model: Direct & Right Angle Viewing
This general purpose fiberscope is designed to be a valuable inspection device which is capable of reducing or eliminating costly machine & equipment teardown for inspection purposes. With the portable battery handle light source, the GP model becomes a self-contained, versatile inspection device to detect worn, damaged, or otherwise inadequate conditions in hidden or normally inaccessible areas.



Specifications:

- Shaft Dia. .312" (7.9mm).
- Shaft Length: 24".
- Min Band Radius: 1.5".
- Field of View: 60 Degrees.
- Depth of Field: 2"-3.0".

Features:

- B-Style, Diopter Adjustable Eyepiece.
- ACMI Light Guide Connector.

Complete with light handle, right angle attachment, and heavy-duty carrying case.

Model No. 16128
Order No. 8616128
Price <input type="text"/>



COMPARATORS AND MAGNIFIERS SERIES 510:



POCKET COMPARATOR

Has a precision ground achromatic lens (3 element, 2 groups), photo etched scale, with 7x magnification.

Order No. 1001975	Price <input type="text"/>
-------------------	----------------------------



ELECTRONIC GAGES SERIES 544:



Highly sensitive gages for fast and accurate positioning. Each gage features three LED indicators which provide 360° visibility. Gages are made of hardened and ground chrome steel and include two batteries.

EDGE FINDER

Highly sensitive for fast and accurate positioning. Lights up on contact. T.I.R. within .0002". 3/4" Shank Diameter. .400 Probe Diameter.

Order No. 5440000	Price <input type="text"/>
-------------------	----------------------------

MEDA - SUPERIOR IMPORT	
Order No. 5440500	Price <input type="text"/>



POCKET COMPARATOR SET

Includes the Model 1975 comparator with the 5 most popular reticles, namely #1,#5,#7,#8, and #12 in fitted case.

Order No. 1001976	Price <input type="text"/>
-------------------	----------------------------



POCKET COMPARATOR



Has a precisely ground achromatic lens (coated 4 elements, 2 groups), photo etched scale with a 10x magnification.

Order No.: 1001983	Price: <input type="text"/>
--------------------	-----------------------------

POCKET COMPARATOR SET

Includes the Model 1983 comparator with the 5 most popular reticles, namely, #1,#5,#7,#8 and #12 in fitted case.

Order No.: 1002004	Price: <input type="text"/>
--------------------	-----------------------------



HEIGHT OFFSET GAGE



For fast and accurate setting and measurement of vertical tool height. Lights up on contact.

Order No. 5440010	Price <input type="text"/>
-------------------	----------------------------

3 DIMENSIONAL ELECTRONIC SENSOR (x, y, z)

- A new concept for fast and accurate "zero" finding, and starting point for all three axes (x,y,z).
- Made of high quality steel hardened to RC60, precision ground on all surfaces.
- Operates in vertical and horizontal position.
- Over travel safety zone in all three axes: x,y - .100", z - .200".
- Shank Diameter .750" +.0000/- .0002".
- Probe diameter .2000", ±.0002".
- "Z" axis to reference surface 2.000" ±.0002
- Repeatability ±.0005".



Order No. 5440020	Price <input type="text"/>
-------------------	----------------------------

FLASHLIGHT MAGNIFIER



With 10x magnification is an excellent instrument. It features a built-in lighting device that works on two 1.5 Volt batteries.

Order No. 1001966	Price <input type="text"/>
-------------------	----------------------------

FLASHLIGHT MAGNIFIER AND COMPARATOR

Combination with 7x magnification consists of a magnifying unit and a section to insert batteries.

Order No. 1001998	Price <input type="text"/>
-------------------	----------------------------

