

## FIBRATEx - NON WOVEN ABRASIVE

SERIES 898:

Most Fibratex products consist of a non-woven web of nylon fibres, impregnated throughout with abrasive grain and bonded with synthetic resins. This design produces a cushioned, three-dimensional material that is extremely pliable and long lasting. The uniform dispersion of abrasive throughout the web provides a continuous supply of new grain as the old grain and fibres wear away during use.

Fibratex products, with their open mesh construction, are waterproof, washable, resilient, conformable, non-loading, non-conductive, non-metallic, and non-rusting. Fibratex wheels are easily preformed to conform to special-shaped workpieces.

Since Fibratex products are designed for use where stock removal is not required, they begin where other abrasives leave off. The relatively non-aggressive nature of nylon and grit inherent in the Fibratex material makes it ideal as a finishing tool. While 60 to 80 grit are considered intermediate sizes in other products, they are considered coarse for Fibratex items.

Fibratex can be used on aluminum, brass, copper, nickel, chrome plate, stainless steel, zinc, titanium, tantalum, ceramics, glass, plastic, fiber-glass, wood, plywood, and other materials. Applications include deburring, cleaning, scrubbing, scouring, blending, polishing, highlighting, deflashing plastics, defuzzing plywood, dulling laminates, removing oxides and rust, scuffing paint before repainting, rubbing sealers, removing raised wood fibres, and imparting satin and decorative finishes.



Used wet or dry, Fibratex products offer the following advantages:

- Controlled cut without stock removal
- Consistent, uniform finish
- Minimized smearing and discoloration of the workpiece (heat is dissipated through the open mesh of the product)
- Increased production; time savings
- Ability to automate operations
- Reduced operator training
- Less maintenance required.
- Greater safety than other methods.
- Conformability to irregular surfaces.

Fibratex web material utilizes either silicon carbide or aluminum oxide abrasive grain. Silicon carbide is sharper, cuts faster, and produces finer scratch patterns on most surfaces. Aluminum oxide is more durable and tends to last longer, produces less discoloration on aluminum, and is more aggressive on certain applications such as hardened steel parts. Fibratex hand pads and rolls are available in a non-abrasive material.

These advantages made Fibratex products an excellent alternative to bristle brushes, set-up wheels, greaseless compounds and steel wool.

## HAND PADS

### SPEC CHECK

Starting Recommendations for Hand Pads							
MORE AGGRESSIVE, ROUGHER FINISH ←						→ LESS AGGRESSIVE, FINER FINISH APPLICATIONS	
74000 Brown Heavy Duty Pad	74600 Gray Blending Pad	77700 Maroon Fast Initial Cut Rate	74700 Maroon A/O General Purpose	79600 Green Scouring Pad	63500 Gray Clean & Finish	74800 Gray Final Shine	45600 White Non-Abrasive
<ul style="list-style-type: none"> <li>• Removing rust oxide</li> <li>• Deburring</li> <li>• Blending</li> <li>• Replaces steel wool &amp; wire brushes in many applications</li> </ul>	<ul style="list-style-type: none"> <li>• Cleaning - aluminum</li> <li>• around welds</li> <li>• glass molds</li> <li>• dies</li> <li>• Light deburring of intricate parts</li> </ul>	<ul style="list-style-type: none"> <li>• Cleaning</li> <li>• Deburring</li> <li>• Corrosion removal</li> <li>• Oxidation removal</li> </ul>	<ul style="list-style-type: none"> <li>• Cleaning</li> <li>• Finishing</li> <li>• Deburring machinery &amp; tools</li> <li>• Rust Removal</li> <li>• Defuzzing wood</li> <li>• Preparing surfaces for painting</li> </ul>	<ul style="list-style-type: none"> <li>• Removing - stains</li> <li>• marks</li> <li>• rust</li> <li>• corrosion</li> <li>• oxidation</li> </ul>	<ul style="list-style-type: none"> <li>• Deburring plastic surfaces</li> <li>• Cleaning fiber-glass partitions</li> <li>• Blending Paint</li> <li>• Scuffing acrylic surfaces</li> <li>• Finishing aluminum doors &amp; windows</li> </ul>	<ul style="list-style-type: none"> <li>• Light cleaning - steel</li> <li>• non-steel</li> <li>• Defuzzing wood</li> <li>• Final rub</li> </ul>	<ul style="list-style-type: none"> <li>• Cleaning glass, fiberglass &amp; porcelain fixtures</li> <li>• Wood highlighting &amp; rubbing between finish coats</li> <li>• Use with liquid detergents</li> <li>• Scratch-free cleaning of stainless steel, chrome, copper &amp; ceramic</li> </ul>

### APPLICATION:

#### White - 45600

For general clean-up, light primer rub down and paint overspray removal. Nonabrasive.

#### Gray - 74800

A micro fine (1000 grit) silicon carbide for light cleaning steel and non-steel, defuzzing wood and final rubbing.

#### Gray - 63500

An ultra fine (600 grit) silicon carbide for denibbing between finish coats, as well as lacquer rubbing.

#### Gray - 74600

A medium silicon carbide, that is open denier, primarily used for all types of blending applications, especially on stainless steel.

#### Green - 79600

An economical pad for general clean up as well as finishing stainless steel in the food processing industry.

#### Maroon - 77700

A very fine aluminum oxide pad with a fast initial cut rate for cleaning, deburring, corrosion and oxidation removal.

#### Maroon - 74700

A very fine (240-360 grit) aluminum oxide for general cleaning and finishing, removal of rust and oxidation from metals, and lightly sanding old paint or new primers.

#### Brown - 74000

A heavy duty (120 grit) aluminum oxide pad for aggressive action where a stiffer, coarser pad is required.

Order No.	Grit/Abrasive	Color	Pads/Case	Price Case
6" x 9"				
45600	Non-Abrasive	White	20	
74800	Micro Fine S/C	Gray	20	
9963500	Ultra Fine S/C	Gray	20	
74600	Medium S/C	Gray	20	
79600	General Purpose	Green	20	
77700	Very Fine A/O Fast Cut	Maroon	20	
74700	Very Fine A/O	Maroon	20	
74000	Medium A/O	Brown	20	
Order No.	Description			Price Each
62709	Hand Pad Holder			

(Continued)

## FIBRATEX - NON WOVEN ABRASIVE

SERIES 898: (Continued)



## FIBRATEX SILICON CARBIDE "SURFACE STRIP" DISCS



### DEPRESSED CENTER WHEELS

#### SURFACE STRIP DEPRESSED CENTER WHEELS

**Applications:** An open web construction allows cleaning and conditioning of a multitude of materials quickly and easily, with very little loading. Excellent for removal of surface rust and residue, corrosion, light weld splatter, dirt, mill scale and other similar surface contaminants.



#### Major applications include:

- Cleaning and conditioning after welding.
- Preparing surfaces before welding
- Painting and epoxy coating removal
- Surface preparation before coatings are applied

Order No.	Grit/Abrasive	Color	RPM	Wheels/ Case	Price Each
<b>4-1/2" x 7/8"</b>					
62615	Extra Coarse S/C	Black	13,300	10	
<b>4-1/2" x 5/8-11"</b>					
62616	Extra Coarse S/C	Black	13,300	10	
<b>7" x 7/8"</b>					
62617	Extra Coarse S/C	Black	8,600	10	
<b>7" x 5/8-11"</b>					
62618	Extra Coarse S/C	Black	8,600	10	

### FLEX-LOC TS SURFACE BLENDING DISCS

**Applications:** Deliver a consistent finish when used to clean, deburr, blend or finish all types of metal, wood and plastic. Can also be used for the removal of light rust, oxides and coatings.



Order No.	Grit/Abrasive	Color	Discs/ Case	Price Each
<b>2"</b>				
62908	Very Fine A/O	Blue	50	
62907	Medium A/O	Maroon	50	
62906	Coarse A/O	Brown	50	
<b>3"</b>				
62911	Very Fine A/O	Blue	25	
62910	Medium A/O	Maroon	25	
62909	Coarse A/O	Brown	25	
<b>4"</b>				
966445	Coarse A/O	Brown	25	

Compatible with Standard Abrasives quick change attachment system.

#### SURFACE STRIP DISCS

##### Benefits:

- Smear resistant formula
- Resist loading
- Quick cleaning and conditioning of surfaces
- Quick, tool-free disc changes allow more grinding time
- Resists loading; extended life
- Can be used on face and edge
- Quick-change replacement



##### Major applications include:

- Preparing surfaces before welding
- Cleaning and conditioning after welding
- Surface preparation before coatings are applied
- Paint and epoxy coating removal

Order No.	Grit/Abrasive	Color	RPM	Wheels/ Case	Price Each
<b>2" Flex-Loc TR</b>					
64097	Extra Coarse S/C	Black	15,500	10	
<b>3" Flex-Loc TR</b>					
64098	Extra Coarse S/C	Black	12,000	10	
<b>4" Flex-Loc TR+</b>					
73903	Extra Coarse S/C	Black	8,000	10	

Order No.	Grit/Abrasive	Color	RPM	Wheels/ Case	Price Each
<b>4" x 1/4"</b>					
9963438	Extra Coarse S/C	Black	8,000	25	
<b>4" x 3/8"</b>					
62614	Extra Coarse S/C	Black	8,000	25	
<b>4" x 1/2"</b>					
27164	Extra Coarse S/C	Black	8,000	25	
<b>6" x 1/4"</b>					
9963439	Extra Coarse S/C	Black	5,500	15	
<b>6" x 1/2"</b>					
27163	Extra Coarse S/C	Black	5,500	15	

### FLEX-LOC TR SURFACE BLENDING DISCS



**Applications:** Deliver a consistent finish when used to clean, deburr, blend or finish all types of metal, wood and plastic. Can also be used for the removal of light rust, oxides and coatings.



Order No.	Grit/Abrasive	Color	Discs/ Case	Price Each
<b>2"</b>				
62914	Very Fine A/O	Blue	50	
62913	Medium A/O	Maroon	50	
62912	Coarse A/O	Brown	50	
<b>3"</b>				
62917	Very Fine A/O	Blue	25	
62916	Medium A/O	Maroon	25	
62915	Coarse A/O	Brown	25	

Compatible with 3M Roloc attachment system.

For back-up pads see page 327.

(Continued)

## FIBRATEX - NON WOVEN

### ABRASIVE

SERIES 898: (Continued)

### CONVOLUTE WHEELS

### CLEAN AND FINISH WHEELS

**Applications:** An open mesh product for cleaning and finishing operations.

These wheels are:

- Used with light/moderate pressure
- Low speed
- Not to be used for deburring

Major applications include:

- General clean-up
- Removal of rust and oxide
- Applying decorative contrast finishes
- Blending weld areas or stainless to a #4 mil finish



### SPEC CHECK

#### Starting Recommendations

← Deburring/Blending/Polishing →		← Cleaning and Finishing →	
Heat Sensitive Applications	Deburring	Medium Grain Finishing	Fine Grain Finishing
Clean & Finish Wheels	Deburr & Finish Wheels Heavy Deburring Wheels	Deburr & Finish Wheels Metal Finishing Wheels	Clean & Finish Wheels

Density	Grit	Abrasive
5 ↑ 6 Softer 7 8 Harder 9 ↓	VF = Very Fine F = Fine M = Medium	S = Silicon Carbide A = Aluminum Oxide

Order No.	Grit/Abrasive	MAX RPM	Whls/Case	Price Each
<b>6" x 1" x 1"</b>				
12526	Medium S/C	3,000	4	
<b>6" x 2" x 1"</b>				
12527	Medium S/C	3,000	2	
<b>6" x 4" x 1"</b>				
12516	Medium S/C	3,000	1	
<b>8" x 2" x 3"</b>				
12548	Medium S/C	2,550	2	

Bushings for these products available, see page 327.

Larger sizes available. See our website or inquire.

### DEBURR AND FINISH WHEELS

**Applications:** A dense product available in four different densities, two minerals and two grit sizes to cover a wide range of deburring, blending, polishing and finishing applications.

Major applications include:

- General deburring
- Polishing stainless steel cutlery
- Polishing golf clubs
- Blending coated abrasive scratch patterns
- Edge radiusing



### METAL FINISHING WHEELS

**Applications:** An open mesh product designed primarily for blending or finishing operations. These wheels are excellent all-round wheels for final metal finishing.

Major applications include:

- Preparing surface for buffing or polishing
- Creating satin finishes on all types of metal surfaces
- Blending and matching #3 or #4 mil finishes
- Removing surface imperfections

Order No.	Grit/Abrasive	MAX RPM	Whls/Case	Price Each
<b>6" x 1" x 1"</b>				
9963441	5-MA	6,000	3	
<b>6" x 2" x 1"</b>				
39326	5-MA	6,000	2	
<b>8" x 1" x 3"</b>				
9963442	5-MA	4,500	3	
<b>8" x 2" x 3"</b>				
9963443	5-MA	4,500	2	

Bushings for these products available.

Larger sizes available. See our website or inquire.

Order No.	Density/ Grit/Abrasive	MAX RPM	Whls/Case	Price Each
<b>6" x 1/2" x 1"</b>				
9933812	7-FS	6,000	4	
12581	8-FS	6,000	4	
33872	9-MS	6,000	4	
<b>6" x 1" x 1"</b>				
12529	6-FS	6,000	3	
9912586	6-MA	6,000	3	
33711	6-MS	6,000	3	
63546	6-FA	6,000	3	
31855	6-VFS	6,000	3	
9912592	7-FA	6,000	3	
12530	7-FS	6,000	3	
12532	7-MA	6,000	3	
12587	7-MS	6,000	3	
12531	8-FS	6,000	3	
9015713	8-MA	6,000	3	
12597	8-MS	6,000	3	
63547	8-FA	6,000	3	
12598	9-FS	6,000	3	
17463	9-MS	6,000	3	
<b>6" x 2" x 1"</b>				
33773	6-MA	6,000	2	
33404	7-MA	6,000	2	
39634	7-MS	6,000	2	
9930233	7-FS	6,000	2	
39462	8-MS	6,000	2	
14754	8-FS	6,000	2	
12617	9-FS	6,000	2	

(Continued)

## FIBRATEX - NON WOVEN ABRASIVE

SERIES 898: (Continued)

### CONVOLUTE WHEELS

### DEBURR AND FINISH WHEELS

**Applications:** A dense product available in four different densities, two minerals and two grit sizes to cover a wide range of deburring, blending, polishing and finishing applications.

**Major applications include:**

- General deburring
- Polishing stainless steel cutlery
- Polishing golf clubs
- Blending coated abrasive scratch patterns
- Edge radiusing



Order No.	Density/ Grit/Abrasive	MAX RPM	Whls/Case	Price Each
<b>8" x 1" x 3"</b>				
9912533	6-FS	4,500	3	
12535	7-MA	4,500	3	
9915383	7-MS	4,500	3	
9963446	7-FS	4,500	3	
9912618	8-MS	4,500	3	
0012534	8-FS	4,500	3	
63549*	9-MS	4,500	3	
12635	9-FS	4,500	3	
<b>8" x 2" x 3"</b>				
39635	7-MS	4,500	2	
33654	7-FS	4,500	2	
12641	9-FS	4,500	2	

Larger diameter wheels available. See our website or inquire.

### HEAVY DEBURRING WHEELS

**Applications:** Ideal for heavy deburring, edge breaking, and removing parting lines on exotic metals.

Order No.	Density/ Grit/Abrasive	MAX RPM	Whls/Case	Price Each
<b>6" x 1/2" x 1"</b>				
33838	9-FS	6,000	4	
<b>6" x 1" x 1"</b>				
29641	8-FS	6,000	3	
33753	8-MA	6,000	3	
31605	9-FS	6,000	3	
<b>8" x 1" x 3"</b>				
31599	8-FS	4,500	3	
43700	8-MA	4,500	3	
33741	9-FS	4,500	3	

Larger diameter wheels available. See our website or inquire.

### DEPRESSED CENTER WHEELS

SERIES 176:

Fully fiberglass reinforced, resin bonded. Suitable for steel and iron.

**Packaging:**  
25 pcs, per size for regular hole.  
10 pcs, per size for threaded hub.



## FIBRATEX ACCESSORIES

SERIES 898:

### BACK-UP PADS

Application

**For Flex-Loc TS Surface  
Blending Discs**

Molded rubber pad with a 1/4" steel shank for quick mounting.

Compatible with Standard Abrasives Quick Change attachment system. Hard density for aggressive cutting action. Medium density for all purpose applications. Soft density for contours and fine finish-ing work. Unique locking device on face provides convenience and quick change.

**For Flex-Loc TR Surface Blending Discs**

Molded rubber pad with a 1/4" steel shank for quick mounting. Compatible with a 3M Roloc attachment system. Medium density for all purpose applications. Unique locking device on face provides convenience and quick change.



**For Flex-Loc TS and TR Surface Blending Discs**

Order No.	Description	MAX RPM	Price Each
<b>2" Diameter</b>			
964624	Hard TS	30,000	
9964198	Medium TS	25,000	
964922	Medium TR	25,000	
<b>3" Diameter</b>			
9961626	Hard TS	20,000	
9964113	Medium TS	20,000	
964626	Soft TS	12,000	
964949	Medium TR	20,000	
<b>4" Diameter</b>			
9964135	Medium TS	12,000	
964655	Medium TR	18,000	

### REDUCING BUSHINGS FOR CONVOLUTE & FLAP WHEELS



Order No.	Bushing Reduces to Arbor Size	For Wheel Dia.	Price/Pair
<b>1" Wheel Center Hole</b>			
925016	3/8"	4" thru 6"	
925017	1/2"	4" thru 6"	
925018	5/8"	4" thru 6"	
925019	3/4"	4" thru 6"	
925020	7/8"	4" thru 6"	
<b>3" Wheel Center Hole</b>			
9980531	1"	8"	Each
9980532	1-1/4"	8"	
9980383	1-1/2"	8"	
9980384	1-3/4"	8"	

Wheel Size	Order No.	Price
4x1/4x5/8	4554161	
4-1/2x1/4x7/8	4555162	
7x1/8x 7/8	4557082	
7x1/8x 5/8-11	4557009	
7x1/4x 7/8	4557162	
7x1/4x 5/8-11	4557169	
9x1/8x 7/8	4559082	
9x1/4x 7/8	4559162	
9x1/4x 5/8-11	4559169	

**MEGA**  
Superior Import